



## 3-IN-1 305

**Feature:**

**Combination shear, brake and roll in one compact machine.**

**Right left hand operation**

**Shear can be used of mild steel,. brass, aluminum, copper, lead, plastic and zinc**

**Brake is equipped with easily removable fingers that permit angle, channel, box and other complex bending operations.**

**Slip rolls are precision turned and ground with wire grooves**

MODEL	3-IN-1/ 305	3-IN-1/ 610	3-IN-1/ 760	3-IN-1/ 1016	3-IN-1/ 1067	3-IN-1/ 1320	3-IN-1/ 1067x1.5	3-IN-1/ 1320x1.5
Bed width(mm)	305	610	760	1016	1067	1320	1067	1320
Max. shearing thickness (mm)	1.0	1.0	1.0	1.0	1.0	1.0	1.5	1.5
Max. bending thickness (mm)	1.0	1.0	1.0	1.0	1.0	1.0	1.5	1.5
Max. bending angle	90°	90°	90°	90°	90°	90°	90°	90°
Max. rolling thickness(mm)	1.0	1.0	1.0	1.0	1.0	1.0	1.5	1.5
Min. rolling dia.(mm)	39	39	39	43	43	43	62	76
Package size (mm)	490x330 x420	840x460 x670	970x450 x680	1350x450 x680	1420x560 x750	1680x560 x750	1540x610 x900	1830x610 x970
N.W./G.W. (kg)	43/45	112/123	153/165	195/212	276/297	349/377	390/440	470/530