

## HRBM50HV Round bending machine

### Features:

The round bending machine can be combined with various mold wheels in order to meet various processing demands.

Horizontal and vertical operation

With standard foot pedal

The Round bending machine features an electric three-roller-wheel structure.







It has the advantage of a two axis drive. The upper axis can be moved up and down to adjust the diameter of the processed work piece.

It can conduct round bending processing for plates, T-shaped materials and so on.

The round bending machine has a standard roller wheel, of which the front two types of roller wheel can be used both vertically and horizontally.

The reversible pedal switch facilitates the operation.

### Main Technical data

	60x40x6 30x15x4	600 900	80x45x6 65x40x5	650 550	100x50x6 500x40x5	500 400
	50x5 30x4	500 500	60x5 50x5	500 500	70x6 40x5	500 400
	50x5 30x4	500 500	60x5 50x5	700 700	70x6 40x5	600 500
	φ30 φ10	650 1100	φ35 φ30	600 650	φ35 φ30	600 650
	50x50x2.5 30x30x2	700 800	60x60x3 40x40x3	600 500	70x70x3 30x30x3	900 500
	50x25x2.5 40x20x2	800 1000	70x50x3 50x40x3	1200 800	80x40x3 50x30x2	800 500

## Special roller

Model	RBM40HV		RBM50 / RBM50HV	
Profile	Size	Min Dia. (mm)	Size(mm)	Min Dia. (mm)
	30x2 35x2	700	30x2 35x2	600
	40x2 45x2		40x2 45x3	
	50x2 55x2		50x2 55x2	
	60x2 65x2		60x2 65x2	
	70x2		70x2	