

HRBM65 Round bending machine

The round bending machine can be combined with various mold wheels in order to meet various processing demands.

Hydraulic Control

Horizontal and vertical operation

With standard foot pedal

The Round bending machine features an electric three-roller-wheel structure.








It has the advantage of a two-

axis drive. The upper axis can be moved up and down to adjust the diameter of the processed work piece.

It can conduct round bending processing for plates, T-shaped materials and so on.

Round bending machine has a standard roller wheel, of which the front two types of roller wheel can be used both vertically and horizontally.

The reversible pedal switch facilitates the operation.

Model	HRBM65HV	
Dia. Of roller(mm)	∅65	
Power	2.25 kW	
Spindle speed	9.3r/min	
Packing Size	125x115x180cm	
N.W./G.W.	720/920KGS	
Capacity	Size	Min Dia.(mm)
	80x25	600
	40x10	500
	120x25	600
	50x10	400
	50	600
	20	400
	80x40x7	500
	40x40x5	400
	80x40x7	400
	40x40x5	360
	100x50x6	600
	50x40x5	500
	100x50x6	600
	50x40x5	500

Special roller

Model	HRBM40HV		HRBM50HV		HRBM65HV	
Profile	Size	Min Dia. (mm)	Size(mm)	Min Dia.(mm)	Size	Min Dia.(mm)
	30x2 35x2	700	30x2 35x2	600	3-1/2"x2"	900
	40x2 45x2		40x2 45x3		2-1/8"x2"	500
	50x2 55x2		50x2 55x2		\varnothing 100x2mm \varnothing 60x2mm	1000
	60x2 65x2		60x2 65x2			500
	70x2		70x2			