

XK7130A CNC milling machine

FEATURES:

- ※XK7136C High-speed spindle unit, the frequency stepless speed regulation
- ※XK7136B5# TURRET MILL-HEAD
- ※Suit for Small parts of the high-precision, highly efficient automatic processing
- ※HNC-18i/21MD, GSK-928MA/983M or KND-100Mi/1000MACNC system

XK7130A VERTICAL CNC MILLING MACHINE

- ※HNC-18i/21MD, GSK-983M or KND-100Mi CNC system
- ※3# TURRET MILL-HEAD
- ※Suit for Small parts of the high-precision, highly efficient automatic processing
- ※Overall structure of compact
- ※Fully functional

SPECIFICATION	UNIT	XK7136C	XK7130A
X-axis travel	mm	900	460
Y-axis travel	mm	360	210
Z-axis travel	mm	480	360
Spindle nose to table	mm	100-580	120-480
Spindle center to column guide-way face	mm	460	200-500
High speed feeding of X, Y, Z axis	mm/min	5000/5000/4000	3000
Feeding speed	mm/min	1-2000	1-2000
Size of table	mm	1250×360	1000×280

Max. loading capacity of table	kg	400	150
T-slot NO./width /distance of table		3×18×80	3×14×63
Spindle speed range/step	r/min	200-4000	66-4540/16
Main motor rated power	kw	5.5	2.2 (3HP)
Spindle hole taper		BT40	7 : 24 ISO30
N.W	kg	2500	1300
Overall dimension	mm	2220×1850×2350	1560×1340×2130