



## X6336V/X6332V/XQ6332V/X6330V Turret milling machin

X6336V/X6332V/XQ6332V/X6330V Turret milling

Driven by servo motor

Table automatic feed on X Y Z

### Automatic rapid feed on X Y Z

specifications		X6336V	X6332V	XQ6332V	X6330V
Table size (mm)		1325/1600x360mm	1325/1600x320	1270/1370x320	1270/1370x300
Table travel	Longitudinal (mm)	750/1300		720/820	
	Cross (mm)	320		300	
	Vertical (mm)	450		400	
Rapid speed of table (X Y Z) (mm/min)		1200/800/600mm/min		1000/1000/750	
Spindle taper (vertical)		7:24 ISO40		7:24 ISO40	
Spindle taper (horizontal)		7:24 ISO50		7:24 ISO40	
Stroke of spindle quill (mm)		127			
Table fed(X,Y,Z) (mm/min)		Variable 30-750/20-500/15-375			
Distance between horizontal nose and table surface (mm)		20-470		75-475	
Distance between spindle axis and table surface (mm)		200-650		275-650	
Spindle speed range (steps) rpm (rpm)		65-4660/8 (V) 60-1800/16 (H)		65-4660/16 (V) 35-1500/12 (H)	
T-slots(No./width/pitch) (mm)		3/18/80	3/14/70	3/14/70mm	
Arm travel (mm)		550	550	450	
Main motor power (Kw)		5.5 (H) 3.75 (V)		3.75(H) 3 (V)	
Overall size (mm)		1800x2100x2500/1520x2100x2500		1720x1680x2350/1820x1680x2350	

N.W (Kg)	2700/2850	2650/2800	1680/1730	1650/170

**Standard accessories**

Drill chuck	drawbar	Work lamp	Milling vice
Coolant system	Chip tray	Toolbox&tools	Operation manual

**Optional accessories**

DRO	vise	Milling collet chuck	Rotary table
Dividing head	58 pcs clamping kits	Keyless drill chuck	