

## **Catalogo JPG TOOLS Maquinaria Industrial**

## XN6330H X6330H XS6330H Milling Machine

## Features of XN6330H X6330H XS6330H Universal Vertical and Horizontal Milling Machine

XN6330H X6330H XS6330H Universal Vertical and Horizontal Milling Machine has super width of bed and knee box guide way, which have been hardened and precision ground, with high rigidity and stability. The guide way of the saddle is lined with TF wearable belt. The machine with one vertical spindle and one horizontal spindle, the spindles and gears have been hardened and ground, suitable heavy cutting.

## Technical Specifications of XN6330H X6330H XS6330H Universal Vertical and Horizontal Milling Machine

Model	Unit	XN6330H	X6330H		XS6	XS6330H	
Table	mm	300x1300	300x1300	300x1500	300x1370	300x1500	
Table longitudinal travel	mm	845	845	1000	880	1000	
Table cross travel	mm	385		380			
Knee vertical travel	mm	435					
Table longitudinal feed rate	mm/min	0-3500					
Table cross feed rate	mm/min	Servo motor					
Knee rapid speed	mm/min	900					
Motor power	hp	5hp Standard: 3hp; optional: 5hp			; optional: 5hp		

Speed		<b>TID 100</b>	Standard/16 steps: 50HZ:65-4500 / 60HZ:80-5440				
	Speed	rpm	Optional: variable speed 60-3600				
	Taper			ISO40		Standard: R8; 0	Optional: ISO40
Vertical	Quill travel	mm	127				
spindle	Quill feed	mm/rev	0.04/0.08/0.15				
Head rotating			R/L: 90°		R/L: 90°;	B/F: 45°	
	Distance from spindle end to table surface	mm	115-545				
	Motor power	hp	5hp 50Hz: 45/80/165/260/500/980; 60Hz: 55/100/200/315/600/1180				
	Speed	rpm					
	Taper		ISO40 -20-410				
Horizontal spindle	Distance from spindle end to table surface	mm					
Distance from spindle end to ram		mm	183				
Ram travel		mm	480				
Ram rotating	g angle		360°				
Net weight		kg	1900 1900 1950 1680 1		1730		

Packing size (L x W x H)	mm	1800x1500x2200	1800x1800x2200	1800x1600x2200	1800x1800x2200

Standard accessories of XN6330H X6330H XS6330H Universal Vertical & Horizontal Milling Machine

Draw bar, Tool box & tools, Working lamp, Electrical cabinet and hang up control panel, Automatic. Lubication pump, Coolant system, Oil tray, plastic splashing guard.

Optional accessories of XN6330H X6330H XS6330H Universal Vertical and Horizontal Milling Machine

X-axis APF500 power feed	6 inch machine vise		
X-axis APF750 power feed	52PCS clamping kits		
Y-axis APF500 power feed	8PCS R8 collets		
Y-axis APF750 power feed	15PCS R8 collets		
Z-axis APF750 power feed	8PCS R8/NT30/NT40 collets		
X-axis Gear box feeder	15PCS R8/NT30/NT40 collets		
Y-axis Gear box feeder	Air-power draw bar		
Variable speed milling head-	Spindle guard		
X/Y-axis SINO	Table guard		
X/Y/Z-axis SINO	Ball screw for X6330/6333		

Optional Variable-frequency Drive, VFD Milling head of XN6330H X6330H XS6330H Universal Vertical and Horizontal Milling Machine

Variable-frequency Drive,		
VFD Milling head	Variable-frequency Drive Brand	Variable-frequency Drive Model

5HP/380V	Yaskawa	3.7KW	
	Schneider	3.7KW	
	Siemens	3.7KW	
	Yaskawa	3.7KW	
5HP/220V	Schneider	3.7KW	
	Siemens	3.7KW	