

Z5045 drilling machine

1. Drilling, milling and tapping
2. Super high column
3. Headstock and worktable up & down perpendicularly

MAJOR SPECIFICATIONS

MODEL	Z5045
Max. drilling capacity	45mm
Spindle taper	M.T.3 or R8/ M.T.4 or R8/ M.T.4 or R8
Spindle travel	130mm
Step of spindle speed	6
Range of spindle speed 50Hz	80-1250r.p.m
60Hz	95-1500r.p.m
Min.distance from spindle axis to column	283mm
Max distance from spindle nose to worktable	725mm
Max distance from spindle nose to stand table	1125mm
Max. travel of headstock	250mm
Swivel angle of headstock (horizontal/perpendicular)	360°/±90°
Max. travel of worktable bracket	600mm
Workable size of availability	380 x 300mm
Swivel angle of table horizontally	360°
Table leaned	±45°
Size of stand worktable of availability	417 x 416mm
Worktable travel (X/Y)	\
Vertical travel of worktable	\
Motor Power	1.5KW
Speed of motor	1400r.p.m
Net weight/Gross weight	430/480(kgs)
Packing size (L x W x H)	1850 x 750 x 1000mm

Features

1. Drilling, milling and tapping
2. Head swivels 360° horizontally
3. Headstock and worktable up & down perpendicularly
4. Super high column
5. Precision micro feed
6. Positive spindle lock

STANDARD ACCESSORIES

- *Wedge*
- *Tie rod*
- *Washer*

OPTIONAL ACCESSORIES

- *Double Speed motor*
- *Bench vice 90mm.125mm,180mm*
- *Milling holder*
- *Drill chuck and arbor*
- *Milling chuck (8PCS)*
- *Heighten column*
- *Coolant system*
- *Working lamp*
- *Auto-Tapping system*
- *Boring bar*
- *Clamping kits (58pcs)*