



ZN4025/ZN4030/ZN4030B/ZN4035/ZN4035A/ZN4035B

Product Description

Standard accessories: Shaft sleeve for taper shank tool, Key type drill chuck, Connecting bar for drill chuck, Wedge for taper shank tool, Double open end spanner

Optional accessories: Ø6-Ø16mm collet, Milling cutter shank, Cross worktable, Collet shank, Nut for T-slot, Inner hexagon bolt, 125mm precision vice, Rotation worktable

Model	ZN4025	ZN4030	ZN4030B	ZN4035	ZN4035A	ZN4035B
Max Drilling diameter(steel) and tapping diameter(mm)	Ø25/M16	Ø30/M20		Ø35/M22		
Max travel of spindle(mm)	110	135		155		
Max distance from spindle to generating line of column(mm)	240	260		320		
Max distance from spindle end to the surface base worktable(mm)	650	700		645		
Max travel of spindle box(mm)	470	520		515		
Spindle taper bore(MT)	3	3		4		
Spindle speed steps	6	12		12		
Spindle speed range(r/min)	125~2825	125~3030		125~3030		
Spindle feed steps			3		3	
Spindle feed range(mm/r)			0.1~0.3		0.1,0.2,0.3	

Dimension of worktable(mm)					
Effective working area of worktable	310x320	335x340		370x360	
Power of motor(kw)	0.75	0.85/1.1		1/1.2	
Max machine dimension(mm)/weight(KG)	700x410x1620 270	750x500x1620 360		850x500x1670 385	