

ZWB5030/35/40/50A

Model	ZWB5030A	ZWB5035A	ZWB5040A	ZWB5050A
Max Drilling dia(steel) and tapping dia(mm)	Ø30/M20	Ø35/M22	Ø40/M24	Ø50/M30
Max milling cutter diameter(mm)	N/A	80	80	80
Max Travel of spindle(mm)	125	155	190	200
Max Distance from spindle to generation line of column(mm)	280	320	340	360
Max Distance from spindle nose to surface of worktable(mm)	650	625	665	590
Max Distance from spindle nose to surface of base worktable(mm)	1120	1180	1195	1175
Max Travel of worktable and bracket/Manual(Mechanical)(mm)	605	560	570(450)	530(410)
Swivel angle of worktable	±45	±45	±45	±45
Spindle taper bore	MT3	MT4	MT4	MT4
Spindle speed steps	Stepless	Stepless	Stepless	Stepless
Spindle speed range(r/min)	70~249,249~3500	65~460,465~3250	60~400,396~2600	50~316,316~2200
Spindle feed steps	3	3	4	6
Spindle feed range(mm/r)	0.1,0.2,0.3	0.1,0.2,0.3	0.1,0.2,0.3,0.4	0.08~0.50
Dimension of worktable(mm)	450x380	500x380	520x440	445x435

Effective working area of worktable	335x340	370x360	405x395	445x435
Power of motor(kw)	1.1	1.5	2	3
Machine dimension(mm)	785x480x2035	849x545x2290	849x545x2290	950x680x2405
Packing dimension/Net weight and gross weight	960x590x2150mm 320/400KG	870x510x2140mm 550/560KG	1000X650X2220mm 550/600KG	1150x680x2250mm 650/705KG