

## ZX40HS drilling machine

<http://www.ycjxie.com> E-Mail: [Sales@ycjxie.com](mailto:Sales@ycjxie.com) [dfzhu@163.net](mailto:dfzhu@163.net)



### Drilling & milling machine

#### Features

- \* Milling, drilling, tapping, boring, reaming.
- \* Headstock swivel 360°
- \* Worktable up & down perpendicularly (ZX40H).
- \* Super high column.
- \* Wide and big table (Z5030).
- \* Micro feed precision.
- \* Heavy-duty tapered roller bearing spindle.
- \* Positive spindle lock.
- \* Adjustable gibs on table.
- \* Geared drive, lower noise.
- \* Equipped with cross table (ZX40H)
- \* Zero voltage safeguard
- \* Optional :tapping system ,double speed motor.

\*Z5030A:equipped with coolant system auto spindle power down feed.

\*Z5035,ZX40HS:equipped with lamp, coolant system, auto power feed,electric box,double speed motor.

#### Standard accessories:

Draw bar, adapter,taper shank for drilling chuck, drilling chuck, arbor, T slot bolt, washer, nut, tilted wedge, spanner,oil gun.

#### Optional accessories:

Double speed motor, auto spindle power down feed, tapping assembly,coolant system, work light, 58PCS clamping tool kit, milling vise, keyless drill chuck,depth indicator,digital readout system.



Model	ZX40H	ZX40HS	Z5030 (Z5030A)	Z5035
Max. drilling capacity	31.5mm(MT3) 40mm(MT4)	31.5mm(MT3) 40mm(MT4)	31.5mm(MT3) 40mm(MT4)	40/35mm
Diameter of vertical milling	32mm	32mm	32mm	24/22mm
Spindle taper	MT3, MT4 or R8	MT3, MT4	MT3, MT4	MT3/MT4/R8/ISO30
Dimension of base	650x450mm	670x470mm	650x450mm	670x470mm
Spindle speeds range	50HZ : 75~1600 60HZ : 90~1970	75~3200r/min	50HZ : 75~1600 60HZ : 90~1970	12steps:75~3200r/min
Distance spindle	272.5mm	310mm	272.5mm	320mm
Worktable travel	X 370mm Y 190mm	X 570mm Y 230mm	-	-
Dimension of worktable	600x190mm	800x240mm	540x470mm	500x360mm
Spindle travel	120mm	130mm	120mm	130mm
Spindle speeds	6	12	6	12steps
Motor	1.1kw	1.5kw	1.1kw	1.5kw
Diameter of column	φ115mm	125mm	φ115mm	125mm
N.W / G.W	340 / 390kg	450/500kgs	320 / 370kg	430/480kg
Max. Distance spindle nose to worktable	610mm	525mm	715mm	685mm
Max. Distance spindle nose to base	1180mm	1140mm	1180mm	1140mm
Package size	820x720x1830mm	570x890x2120mm	740x720x1830mm	570x810x2110mm