

Z5032 gear driven drilling

Drilling, tapping, boring,reaming:

Strong column ,gear drive,low noise;

Heavy-duty tapered roller bearing spindle, positive spindle lock.

Drilling machine Z5025 is equipped with spindle manual feed,

Drilling machine Z5035 is equipped with spindle auto power down feed,

Equipped with cooling system,working light, 2 step motor with 12 steps speed which can improve the machining accuracy and producing efficiency

Standard accessories:

Adaptor, drilling chuck,elevating lever,oil gun, screw, washer, tools."CE" protecting arbor, cooling system,lamp

Optional accessories:

Depth indicator, 58pcs steel clamping kit, machine vise.

| Item | Z5025 | Z5032 |
|--|-----------------------|-----------------------|
| Max. Drilling dia (Steel/Iron) | 28/25mm | 32/25mm |
| Max. tapping dia.(Steel/Iron) | 22/18mm | 22/16mm |
| Spindle taper | MT3 | MT4 |
| Worktable Size | 380×380mm | 460×460mm |
| Base size | 535×360mm | 620×450mm |
| Width of T-slot | 14mm | 14mm |
| Distance of T –slot base | 160mm | 160mm |
| Spindle stroke | 130mm | 160mm |
| Diameter of column | 125mm | 125mm |
| Distance from spindle center to column surface | 250mm | 300mm |
| Distance from spindle nose to worktable | 825mm | 720mm |
| Distance spindle nose to base | 1200mm | 1200mm |
| Vertical travel of worktable | 700mm | 700mm |
| Spindle speeds range | 75~3200rpm(12 speeds) | 75~3200rpm(12 speeds) |
| Speed power feed range | | 0.06/0.12/0.18mm/r |
| Motor(2 speed motor) | 1kw/0.85kw | 1.5kw/1.1kw |

| | | |
|--------------|----------------|----------------|
| Packing size | 2100×400×640mm | 2100×400×640mm |
| Net weight | 210kgs | 350kgs |