

AD08X AD10X AD15X AD20X Slant Bed CNC Lathe

ITEM	UNIT	AD08X	AD10X	AD15X	AD20X		
CAPACITIES							
Swing over bed	mm	420		450	500		
Swing over carriage	mm	160		220	250		
Max.Dia. of workpiece	mm	340	360	400	420		
Max.length of turning	mm	250	500	450	750/1000		
Angle of bed	¡ã	45					
Span of guideway	mm	362		400			
FEED							
X-axis travel	mm	180	230	230	250		
Z-axis travel	mm	330	530	530	850		
Ball screw of X		3208-C3					
Motor torque of X	NM	iÝ7.5	jÝ10				
Ball screw of Z		3210-C3	3208-C3		4010-C3		
Motor torque of Z	NM	jÝ10					
SPINDLE							
Max.spindle speed	rpm	4500					
Spindle bore	mm	56		61			
Spindle nose		A2-5		A2-6			
Taper hole		1:20					
Main power	kw	5.5		7.5	11		
Hydraulic chuck		6/46		8/52	8		
TURRET							
No. of turret		8					
Indexing time	s	0.5					
Size of turret	mm	25x25					
TAILSTOCK							
Dia. of tailstock	mm	72					
Travel of tailstock	mm	100					
Quill of taper hole		MT4					
OTHERS							

Accuracy and roughness		IT6/Ra0.8¦Ìm					
Weight	kg	3000	3500	3550	4000		
Length	mm	2130	2560	2560	2950		
Width	mm	1500	1500	1500	1500		
Hight	mm	1700	1730	1730	1730		
CNC system		GSKGSK988TA/ HNC-808					