



## CQ6230A Bench Lathe

<b>Feature:</b>			
-----------------	--	--	--

Precision ground and supersonic frequency hardened bed ways.  
 The spindle is supported with precision roller bearing.  
 Strong power motor suited for heavy duty cutting.

### UNIVERSAL MECHANICAL PRECISION LATHE

Model	CQ6230A	CQ6230A-1	CQ6230A-2
Max.swing over bed	Φ310mm		
Max.swing over cross slide	Φ180mm		
Max. swing over gap	Φ450mm		
Distance between centers	750mm/910mm/1000mm		
Width of bed	181mm		
Spindle bore	Φ38mm		
Taper of spindle bore	M.T.#5		
Range of spindle speeds	65-1810(1400)rpm		
Taper of tailstock	M.T.#3		
Metric threads can be cut	0.4-7mm		
Inch threads can be cut	4-60 T.P.I.		
Range of longitudinal feeds	0.0527-1.2912mm/rev		
Range of cross feeds	0.011-0.276mm/rev		
Max. travel of cross slide	130mm		
Max. travel of top slide	75mm		
Max. travel of tailstock quill	100mm		

Motor power	1.1KW.3PH/1.5KW.1PH	
<b>Standard accessories :</b>	<b>Optional accessories :</b>	
3 Jaw chuck( $\Phi$ 160mm)	4 Jaw chuck( $\Phi$ 200mm)	
Change Gears Set	Face Plate	
M.T.#3 Dead Centers	Steady Rest	
M.T.#5/3 Reduction Sleeve	Follow Rest	
Oil gun	Work Light	
Splash Guard	Foot Brake System	
Foot stands	Coolant System	
Tool Box&Tools	Live Center	
Oil Tray	Drill Chuck+Drill Arbor	
	Leadscrew Guard	
	Chuck Guard	
	Localizer	
	Clutch For Feed Rod	
	Quick Change Tool Post	
	Digital Readout(2 Axis)	