



## CY6260 Lathe

Model No.	CY6260	CY6266	CY6280
<b>Specifications</b>			
Distance between centers	1000/1500/2000/3000 mm		
Bed width	400 mm		
Swing over bed	600 mm	660 mm	
Swing over gap	800 mm	860 mm	
Swing over cross slide	400 mm	460 mm	
Spindle nose	ISO-C11 or D11		
Spindle bore	103mm		
Range of spindle speeds	forward rotation 9-1275 rpm/18 reverse rotating 16-816 rpm/6		
Range of cross feeds	0.036-2.033 mm/r 72 kinds		
Range of longitudinal feeds	0.073-4.066mm/r 72 kinds		
Range of inch threads	56-1/4 T.P./72		
Range of metric threads	0.5-112 mm/72		
Range of moduler threads	0.5-7 mm/36		
Range of diametrical threads	56-4 D.P/36		
Top slide travel	110 mm		
Cross slide travel	325 mm		
Tailstock quill travel	150 mm		
Tailstock quill diameter	90 mm		
Tailstock quill taper	MT6		
Main motor	7.5kw	7.5kw	11kw
Rapid feed motor	0.25 kw		
Coolant pump motor	90W		
Packing size	2820/3320/3820/4820x1300x1650 mm		
Net weight	2900/3150/3400/3800kg 3500/3750/4050/4450 kg		

Standard Accessories	Optional Accessories
3-jaw chuck (325mm)	Quick change tool post
4-jaw chuck (400mm)	Turning tools
Face plate	Leadscrew cover
Steady rest	Chuck guard
Follow rest	Tool post cover

Splash guard	Digital readout system
Stand & oil tray	Taper turning attachment
Halogen work lamp	Rapid moving attachment
Toolbox & tools	
Coolant system	
Foot brake	