



C6250B C6266B Engine Lathe

Model No.	C6250B	C6266B
Swing over bed	500 mm	660 mm
Swing over carriage	310 mm	420 mm
Swing over gap	720 mm	870 mm
Distance between centers	1000/1500/2000/3000 mm	
Bed width	405 mm	
Spindle bore	80 mm	
Taper of spindle bore	MT7	
Step of spindle speeds	12	
Range of spindle speeds	36-1600 rpm	
Range of cross feeds	0.027-1.07 mm/r	
Range of longitudinal feeds	0.063-2.52 mm/r	
Range of inch threads/No.	28-2T.P.I. 26kinds	
Range of metric threads/No.	1-14mm 22kinds	
Threads diametrical pitches	56-4 D.P. 24kinds	
Threads module pitches	0.5-7 M.P. 18kinds	
Rapid feed of cross traverse	1.9 m/min.	
Rapid feed of longitudinal traverse	4.5 m/min	
Top slide travel	145 mm	
Cross slide travel	340 mm	360 mm
Max. size of tool (WxH)	25x25 mm	
Tailstock quill travel	150 mm	
Tailstock quill diameter	75 mm	
Taper of tailstock quill	MT5	
Motor	7.5 kw	

Packing size	2500/3000/3500/4500x1100x1650 mm	
Net weight	2750/3000/3250/3600/ kg	3000/3200/3400/3900 kg

Standard Accessories	Optional Accessories
3-jaw chuck (250mm)	Quick change tool post
4-jaw chuck (320mm)	Turning tools
Face plate	Leadscrew cover
Steady rest	Chuck guard
Follow rest	Tool post cover
Splash guard	Digital readout system
Stand	Taper turning attachment
Halogen work lamp	One piece casting stand
Toolbox & tools	
Coolant system	
Foot brake	
Five position carriage stop	