



C6250C Lathe

Item	Model	C6136C C6236C	C6140C C6240C	C6150C C6250C
CAPACITY	Max. swing over bed (mm)	360	400	500
	Max. swing over cross slide (mm)	190	230	330
	Max. swing in gap (mm)	520	560	660
	Center distance	750;1000;1500mm		
	Bed width	360mm		
SPINDLE	Spindle hole	52mm		
	Spindle nose	C6		
	Spindle taper	MT6		
	Spindle speeds (Number)	40-1400rpm (9Steps), 1600rpm optional		
FEEDS	Metric threads range(Kinds)	0.25-14mm (20 Kinds)		
	Inch threads range (Kinds)	2-40/inch		
	Module threads range (Kinds)	0.5-3.55mm(11Kinds)		
CARRIAGE	Cross slide travel	180mm		222mm
	Compound rest travel	95mm		
	Cross-section size of toolshank	20*20mm ²		
	Taper of tailstock sleeve	MT4		
TAILSTOCK	Dia. of tailstock sleeve	65mm		
	Travel of tailstock sleeve	140mm		
Main motor power	4kw			5.5kw
Packing size (L*W*H) (mm)				
Center distance: 750mm	2220*1150*1590mm			
1000mm	2470*1150*1590mm			
1500mm	2970*1150*1590mm			
Net Weight/Gross Weight				
Center distance: 750mm	1350/2000	1400/2050	1500/2150	
1000mm	1450/2100	1500/2150	1600/2250	
1500mm	1600/2250	1650/2300	1750/2400	