



CW61128/148/168 /198/208

MODEL	CW61108	CW61128	CW61148	CW61168	CW61198	CW61208
Max workpiece weight	10吨					
Max swing over bed	1080mm	1280mm	1480mm	1680mm	1980mm	2080mm
Max swing over cross slide	600mm	800mm	1000mm	1200mm	1500mm	1600
Center distance	2m 3m 4m 5m 6m 8m 10m 12m					
Max swing over gap	1420mm	1620mm	1820mm	2020mm	2320mm	2420mm
Valid length of gap	600mm					
Bed width	1100mm					
Headstock						
Spindle bore	φ130mm					
Spindle taper	公制140#					
Spindle speeds	3.15-315r/min或2-200r/mm或2.5-250r/mm.转数 种数 : 正21种, 反12种					
GEAR BOX-THREADS & FEEDS						
Metric threads range	44种 1-120mm					
Inch threads range	31种 1/4-24牙/时					
Moudle threads range	45种 0.5-60mm					
Diametral threads range	38种 1/2-56DP					
Longitudinal feeds range	56种 0.1-12mm					
Cross feed range	56种 0.05-6mm					
Rapid feed:long/cross	1200mm/min,1800mm/min					
TOOL POST						
Distance between Center&Tool	48mm					
Tool section	45*45mm					
CARRIAGE						
Cross slide travel	860mm					
Compound rest travel	280mm					
TAILSTOCK						
Sleeve diameter	φ260mm					
Sleeve taper	公制80#					
Sleeve travel	300mm					
MOTOR						
Main drive motor	30kw					
Coolant pump motor	0.15kw					
Rapid feed motor	1.5kw					
Tailstock motor	1.5kw					
Center distance:Net weight.Dimention CW61148	2000	18000kg		5280*2200*2600		
	3000	19000kg		6280*2200*2600		
	4000	20000kg		7280*2200*2600		

	5000	21000kg	8280*2200*2600
	6000	22000kg	9280*2200*2600
	8000	24000kg	11280*2200*2600
	10000	26000kg	13280*2200*2600
	12000	28000kg	15280

Remark: the workpiece limit Load:10 TONS.

spindle bore 130mm,bed width 1100mm