

CWQ61110/125/140/160

型号	MODEL	CWQ61100	CWQ61125	CWQ61140	CWQ61160
机床最大承重	Max. weight of workpiece	8T			
床身上最大回转直径	Max. swing over bed	1000mm	1250mm	1400mm	1600mm
横拖板上最大回转直径	Max. swing over cross slide	620mm	870mm	1000mm	1100mm
两尖顶距离	Center distance	1.5m 2m 3m 4m 5m 6m 8m 10m 12m			
床身宽度	Width of bed	780mm			
床头箱	HEAD STOCK				
主轴孔径	Spindle hole	φ130mm			
主轴锥孔	Spindle taper	公制140#			
主轴转速范围	Spindle speeds	3.15-315r/min或2.5-250r/mm. 转数 种数: 正21种, 反12种			
进给箱	GEAR BoX-THREADS&FEEDS				
公制螺纹范围 (种数)	Metric threads range (kinds)	44种 1-120mm			
英制螺纹范围 (种数)	Inch threads range (kinds)	31种 1/4-24牙/吋			
模数螺纹范围 (种数)	Moudle threads range (kinds)	45种 0.5-60mm			
经节螺纹范围 (种数)	Diametral threads range (kinds)	38种 1/2-56DP			

纵向主轴每转进给量范围	Longitudinal feeds range(kinds)	56种0.1-12mm		
横向主轴每转进给量范围	Cross feed range(kinds)	56种 0.05-6mm		
快速进给：纵向/横向	Rapid feed:Long/Cross	1200mm/min, 1800mm/min		
刀架	TOOL-POST			
主轴中心至刀具安装面距离	Distance between Center & Tool	48mm		
刀具截面	Tool section	45*45mm		
拖板	CARRIAGE			
滑板最大横向行程	Cross slide travel	650mm		
小刀架最大行程	Compound rest travel	250mm		
尾座	TAILSTOCK			
尾座套筒直径	Sleeve diameter	φ160mm		
尾座套筒锥度	Sleeve taper	公制80#或莫氏6#		
尾座套筒最大行程	Sleeve travel	300mm		
电机	MOTOR			
主电机	Main motor	22kw		
冷却泵电机	Coolant motor	0.15kw		
快速进给电机	Rapid feed motor	1.5kw		
两尖顶距.净重.外形尺寸CW61125	Center distance.Net weight.Dimention CW61125	1500	11400kg	4200*1900*2400
		2000	12200kg	4700*1900*2400
		3000	13000kg	5700*1900*2400
		4000	13800kg	6700*1900*2400
		5000	14600kg	7700*1900*2400
		6000	15400kg	8700*1900*2400

		8000	17000kg	10700*1900*2400
		10000	18600kg	12700*1900*2400
		12000	20200kg	14700*1900*2400

*Remark: the workpiece limit Load: 8 TONS.
spindle bore 130mm,bed width 780mm*