



**CW6263F/CW6280F/CW6295F**

MAIN SPECIFICATION	CW6163F	CW6263F	CW6180F	CW6280F	CW6195F	CW6295F
MAX SWING OVER BED	630MM		800MM		950MM	
MAX. SWING OVER CARRIAGE	350MM		520MM		640MM	
MAX SWING IN GAP		800MM		970MM		1120MM
LENGTH OF GAP		390MM		390MM		390MM
MAX LENGTH OF WORKPIECE	1000, 1500, 2000, 3000, 4000, 5000, 6000, 8000,10000MM					
SPINDLE BORE	105MM					
TAPER IN SPINDLE BORE(1:20)	METIC 120MM					
RANGE OF FORWARD SPINDLE SPEEDS	6-800R/MIN, 18 KINDS					
RANGLE OF LONGITUDINAL FEEDS	0.1-24.3MM/R, 64 KINDS					
RANGE OF FINE LONGITUDINAL FEEDS(WITH CHANGE GEARS)	0.05-12.15MM/R					
CROSS EQUAL TO 1/2 LONGITUDINAL FEED	0.05-12/5MM/R(0.00197-0.48IN/R)					
RAPID TRAVERSE OF CARRIAGE	4000MM/MIN					
THREAD CUTTING:						
METRIC THREADS	1-240MM. 50 KINDS					
WHITWORTH THREADS	14-1 TPI, 26 KINDS					
MODULE THREADS	0.5-120MM, 53 KINDS					
DIAMETRAL PITCH THREADS	28-1D.P 24 KINDS					
TAPER CENTER	MORSE NO.5					
MOTOR POWER	11KW					