



Catalogo JPG TOOLS Maquinaria Industrial

JFC21series high-speed & high-precision press

JFC21series high-speed & high-precision press

- ◆ Suitable in such fields as air conditioner fins, exchanger of auto water tank, meter cooler and exchanger of air conditioner, steel plate coiler, silicon steel sheet, and so on.
- ◆ Combined pneumatic friction clutch and brake.
- ◆ JFC21-45 and above type equipped with lifting balance cylinder.
- ◆ Duplex valves imported.
- ◆ Electric compelling oil lubrication system.
- ◆ Concentrated control by PLC with international brand.
- ◆ Buttons, indicators, AC contactors, air circuit breakers and other controlling devices are imported from international brand
- ◆ Equipped with hydraulic overload protecting device.
- ◆ JFC21-25~45 adopts manual shut height adjustment with scale display. JFC21-63 and above type adopts electric shut height adjustment with digital display.
- ◆ This press can be equipped with several shearing valves, ejecting valves and automatic feeding machines to form automatic production line and can replace imported products.
- ◆ None postfix indicates the machine adopts common guide and rigid protector.
- ◆ Suffix “A” indicates the press adopts roller guide and rigid protector.
- ◆ Suffix “B” indicates the press adopts roller guide and hydraulic protector.

	JFC21-25	JFC21-45	JFC21-63	JFC21-80	JFC21-110	JFC21-125	JFC21-160	JFC21-200
	JFC21-25A	JFC21-45A	JFC21-63A	JFC21-80A	JFC21-110A	JFC21-125A	JFC21-160A	JFC21-200A
	JFC21-25B	JFC21-45B	JFC21-63B	JFC21-80B	JFC21-110B	JFC21-125B	JFC21-160B	JFC21-200B

Capacity	kN	250	450	630	800	1100	1250	1600	2000
Nominal Stroke	mm	1.6	1.6	2	2	2	2	2	2
Slide Stroke	mm	30	50	50	40	40	40	40	40
SPM	min ⁻¹	120-200	120-200	120-200	120-180	100-150	100-150	90-120	70-100
Max. Die Height	mm	250	300	300	320	350	350	350	350
Die Height Adjustment	mm	50	50	60	60	60	60	60	80
Between Slide Center & Frame	mm	250	300	300	310	350	350	380	390
Bolster (FB×LR)	mm	480×700	570×800	580×860	600×1000	680×1150	680×1150	740×1300	760×1400
Bolster Opening	mm	300×300	350×350	350×350	260×520	350×480	350×480	φ470	φ470
Bolster Thickness	mm	80	100	110	120	140	140	150	160
Slide Area (FB×LR)	mm	250×360	340×410	400×480	420×560	500×650	540×680	580×770	600×800
Shank Hole (Dia.×Dpth)	mm	φ40×60	φ40×60	φ50×80	φ50×80	φ60×80	φ60×80	φ65×90	φ65×90
Between Columns	mm	450	540	600	680	760	760	830	870
Main Motor Power	kW	4	5.5	7.5	11	15	15	18.5	22
Outline Size (FB×LR×H)	mm	1830×1120×2080	2020×1220 ×2280	1800×1210 ×2520	1850×1280 ×2850	2010×1430 ×3040	2010×1480 ×3040	2280×1540 ×3240	2500×1580 ×3320
Net Weight	kg	3500	4200	6100	8000	11000	11800	15500	16500